# Yeast Raised Donut Frying Guide



## **Frying Instructions**

#### 1. Thaw Donuts

a.) Thaw donuts on frying screen at room temperature for approximately 60 minutes. Be sure donuts are completely thawed before proofing.

Or

- b.) Thaw covered overnight in a cooler. Allow 15-20 minutes to warm to room temperature before proofing.
- 2. Proof for about 35-40 minutes at 95-110° and 75-80% humidity. Proofed donuts should be approximately twice frozen size.
- 3. If donut is moist on the surface when proofed, let sit on rack at room temperature for 5-10 minutes to dry.
- 4. Fry at 375° for 50-60 seconds per side, depending on desired finished exterior color.
- 5. When second side is golden brown, quickly turn all donuts again and remove from fryer immediately. Drain.
- 6. Glaze donuts within 1 to 1 1/2 minutes of frying. Sugar while warm or ice when cool.

# Troubleshooting Guide

#### Problem

#### 1. Large Blister or Air Pocket

- A. Under-proofed
  - B. Proofer has too much moisture
- C. Insufficient drying
- D. Frying temperature too high

#### 2. Excessive Shortening Absorption

- A. Frying Temperature too low
- B. Shortening breakdown or dirty
- C. Over-proofing
- D. Proofer has too much moisture

#### 3. Crust Color Too Dark

- A. Frying temperature too high
- B. Shortening breakdown
- C. Frying time too long
- 4. Crust Color Too Light
  - A. Frying temperature too low
  - B. Frying time too short
- 5. Raw Donut
  - A. Frying temperature too low
  - B. Frying time too short

#### 6. Donuts Balling

- A. Dry-proof
- B. Under-proof
- 7. Excessive Spreading
  - A. Proofer has too much moisture
  - B. Frying temperature too low
  - C. Shortening broken down D. Low shortening level
  - E. Over-proofed

- A. Increase proofing time
- B. Reduce humidity

Suggested Remedy

- C. Allow longer drying time
- D. Reduce fryer temperature
- A. Calibrate and adjust
- B. Filter or replace shortening
- C. Decrease proofing time
- D. Reduce humidity
- A. Calibrate and adjust
- B. Filter or replace shortening
- C. Check Frying time (do not fry by color)
- B. Check Frying time (do not fry by color)
- A. Calibrate and adjust
- B. Check Frying time (do not fry by color)
- A. Increase humidity
- B. Increase proofing time
- A. Reduce humidity
- B. Increase shortening temperature
- C. Filter or replace shortening
- D. Add shortening
- E. Decrease proofing time



### A. Calibrate and adjust

